

*The ability to print labels  
on demand anytime, anywhere*



Optional accessories



Battery & Charger



Touch Scanner



Pen Scanner



PCMCIA Card

# HT200e Thermal Stand-alone Printer

**HT200e**

- Stand-alone / On-line Operation
- Template And Free Formats Useful For Your Selection
- For Mark-Downs (Including Currency Conversion) And Automatic Calculation
- Perfect For Specialty And In-Store Needs
- Casing Made of Inorganic Antimicrobial, High Heat-resistant Material

# HT200e

## General Specifications:



The Expert's Choice in  
Retail and Specialty  
In-Store Applications

<b>Print Method</b>	Direct Thermal
<b>Print Resolution</b>	203dpi (8dot/mm)
<b>Print Speed</b>	60 or 80mm/s, 60mm/s when used with battery (2.4"/s or 3.1"/s)
<b>Max. Print Area</b>	W48mm x L96mm (W1.89" x L3.78")
<b>Media Type</b>	Roll, die-cut label with pre-printed sensing eye-marks. 2 Colour Direct Thermal - Black/Red
<b>Media Size</b>	Width: 25 ~ 48mm (0.98" ~ 1.89")      Backing Paper size: 28 ~ 51mm (1.1" ~ 2.01") Length: 13 ~ 100mm (0.51" ~ 3.94")      Backing Paper size: 16 ~ 103mm (0.63' ~ 4.06")
<b>Media Calliper</b>	0.14 ~ 0.19mm (Thickness)
<b>Media Specifications</b>	Max. outer diameter: 75mm (2.95"), Inner diameter of roll: 26.5mm (1.1"), Wind: Face out
<b>Sensor Type</b>	Reflective sensor for use with pre-printed sensing eye-marks
<b>Interface Choices</b>	For on-line data transmission and scanner interface: RS-232C
<b>Barcode Symbologies</b>	EAN8, EAN13, UPC-A/E, * For the following barcodes, only available at Free mode, NW - 7, Inter-leaved 2 of 5 (ITF), CODE 39, CODE 128 [Subset B (without control codes)/Subset C]
<b>Matrix Fonts</b>	X1: Width 20 x Height 50 Dots (Alphanumeric, Symbol) X2: Width 8 x Height 20 Dots (Alphanumeric, Symbol) X3: Width 13 x Height 21 Dots (Alphanumeric, Symbol) OCR-B: Width 20 x Height 24 Dots (Numeric, English capital letters) Price Font: Width 16 x Height 24 Dots (Numeric, currency mark) POP1: Width 28 x Height 48 Dots (Numeric, currency mark) POP2: Width 48 x Height 68 Dots (Numeric, currency mark) POP3: Width 26 x Height 56 Dots (Numeric, currency mark)
<b>Functions</b>	Self Diagnosis Checking: Cover open, Paper end, Head check, Test print, Battery check Memory backup battery check (Backup battery life is 10 years) PC card battery check (Memory card battery life is 2 years) Operational Panel Switch: FNC1, FNC2, FMT, PGUP, RCL, AC, 0~9. SHFT, SET, FEED, S/S, ENTR, DEL, DATE, #, \$, !, " LCD: Alphanumeric display 16 Characters x 3 Lines with back-light Memory Storage: Fixed FMT: 29      Free FMT: 15 Preset      Approx. 300 (Internal Memory) Approx. 2000 (Option: 2MB SRAM card memory)
<b>Dimension (Printer)</b>	W 132mm x D 230mm x H 151 mm (W 5.2" x D 9.2" x H 6") Weight: approx. 2.5kg (With battery installed), approx. 2.4kg (With Power Supply unit installed)
<b>Dimension (Adaptor)</b>	W 130mm x D 117mm x H 28mm (W 5.2" x D 6" x H 1.1") Weight: 330g
<b>Power Requirements</b>	Input voltage: AC 110 / 230V 10% Output voltage and current: DC8.4V 3.2A Power Consumption: Maximum 71 VA 43W
<b>Environment</b>	Operating: 41 ~ 104°F (5 ~ 40°C) non-condensing; 30 - 80% Storage: 23 ~ 140°F (-5 ~ 60°C) non-condensing; 30 - 90%
<b>Regulatory Approvals</b>	CE Marking, TUV, UL, CSA, CCC
<b>Options</b>	Battery; Battery charger; PCMCIA Card; Rewinder; Unwindæ; Touch/Pen scanner; RS-232C Cable; RS-232C Extension cable



110, Ravi Industrial Estate, Off Mahakali Caves Road, Andheri (E), Mumbai - 400 093.  
Tel: 91-22-6581 4330/31/32 Fax: 91-22-2687 6495

<http://www.intercodesolutions.com>